



**ARMOUR**  
FIRE SAFETY



**WET CHEMICAL**



Meets or exceeds:  
ANSI/UL 8 & 711

English / Spanish labels



Meets or exceeds:  
CAN/ULC-5554 & 5508

English/ French labels

## Built tough and easy to service

### STRIKE FIRST

Wet Chemical fire extinguishers are designed for:



#### **CLASS A**

wood, paper, cloth



#### **CLASS K**

restaurant, kitchen hazard

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Factory filled and pressurized

Complies with NFPA 10 Standard

Meets D.O.T. Requirements

Temperature range: 35°F to 120°F (2°C to 49°C)

5 Year Warranty



CAPACITY	1.6 gallons (6 litres)
UL Model No.	SF-6LK
ULC Model No.	WBDL-6LK
UL Rating	1-A : K
ULC Rating	1-A : K
Range	8 - 10 ft (2.4 - 3 m)
Discharge Time	55 sec
PSI	100
Height	21 1/2" (54.6 cm)
Width	8 3/4" (22 cm)
Diameter	7 1/8" (18 cm)
Weight	24 1/2 lb (11.1 kg)
Standard Bracket	Wall

The STRIKE FIRST Class K extinguisher is designed for use on restaurant or commercial cooking appliances. The low Ph wet chemical agent effectively smothers and cools fires involving combustible cooking oil (vegetable) or animal fat.

It is intended to be used as a back-up for an automatic fire suppression system.