



ARMOUR
FIRE SAFETY



WATER



Meets or exceeds:
ANSI/UL 154 & 711

English / Spanish labels



Meets or exceeds:
CAN/ULC-5503 & 5508

English/ French labels

Built tough and easy to service

STRIKE FIRST
Water fire extinguishers
are designed for:



CLASS A
wood, paper, cloth

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Schrader valve for pressurizing

Complies with NFPA 10 Standard

Meets D.O.T. Requirements

Temperature range: 40°F to 120°F (4°C to 49°C)

5 Year Warranty



CAPACITY	2.4 gallons (9 litres)
UL Model No.	SF-PW250
ULC Model No.	WBDL-PW250
UL Rating	2-A
ULC Rating	2-A
Range	40 ft (12.2 m)
Discharge Time	40 sec
PSI	100
Height	25" (63.5 cm)
Width	8 3/4" (22 cm)
Diameter	7 1/8" (18 cm)
Weight	7.9 lb (3.6 kg)
Standard Bracket	Wall

The STRIKE FIRST water extinguisher is an ideal choice for Class A fire hazards. The powerful stream of water allows it to reach areas other extinguishers cannot.

An effective extinguisher for Class A fires in areas such as warehouse, agriculture and industrial locations.