



FE-36™ CLEAN AGENT FIRE EXTINGUISHERS

SIZES 2.5 LB. (1.1 KG) TO 13.25 LB. (6.0 KG)

FEATURES

- UL Listed
- FE-36 agent is EPA accepted (SNAP) – zero ozone depletion potential and no scheduled phase-out
- Clean agent is safe for delicate electronics – nonconductive, residue-free, no thermal shock
- Meets FAA minimum performance standard (MPS) for handheld fire extinguishers on civilian transport category aircraft (FE-05, FE-09 and FE-13 ONLY)
- Very low in toxicity – LOAEL of 15% is above extinguishing concentration
- Seamless welded steel shell with tough polyester-urethane finish
- Suitable for use in temperatures from –40 °F to 120 °F (–40 °C to 49 °C)
- Optional multipurpose strap brackets available
- Six-year limited warranty



006677

PART NO.	MODEL	RATING	RANGE	CAPACITY	DISC. TIME	DIA.	WIDTH	HEIGHT
551965	FE-02	2-B:C	8-10 ft. (2.4-3.0 m)	2 1/2 lbs. (1.1 kg)	9.0 seconds	3.38 in. (8.6 cm)	5.75 in. (14.6 cm)	14.25 in. (36.2 cm)
551966	FE-05	5-B:C	10-12 ft. (3.0-3.7 m)	4 3/4 lbs. (2.2 kg)	8.6 seconds	4.44 in. (11.3 cm)	8.5 in. (21.6 cm)	17 in. (43.2 cm)
551967	FE-09	1-A:10-B:C	14-16 ft. (4.3-4.9 m)	9 1/2 lbs. (4.3 kg)	9.5 seconds	7 in. (17.8 cm)	9 in. (22.9 cm)	18.75 in. (47.6 cm)
551968	FE-13	2-A:10-B:C	14-16 ft. (4.3-4.9 m)	13 1/4 lbs. (6.0 kg)	13.5 seconds	7 in. (17.8 cm)	9.5 in. (24.1 cm)	22.5 in. (57.2 cm)

Underwriters Laboratories Inc. Listed, U.S.C.G. and FAA (except 2 1/2 lb.) Approved

CLASS **A** **B** **C** FIRES

www.armourfiresafety.com